

Product Data Sheet

Fellert Even Better 1

Product Description

Acoustical plaster made from recycled cotton fibers and perlite. Use as base coat for all the finishes. Use as the top coat for the Sahara and Secern finish. The plaster is sprayed on approx. 3 mm (1/8") wet thickness (base coat).

Packaging: 5 kg (11 pounds) bags.

Installation

The Even Better Acoustical Plaster is mixed with water and applied with a spray machine and troweled to an approximate thickness of 3 mm (1/8").

Base Coat Coverage: 10 m² (100 sqft) per bag.

Sahara Finish Coverage: 20-40 m² (200-400 sqft) per bag.

Secern Finish Coverage: 15-30 m² (150-300 sqft) per bag.

Calculated waste: 5%

Properties

Comprised of 40% recycled material

Powder products unaffected by frost

Pot Life of 12-18 hours

Shelf Life 2 years

Storage

Store in an enclosed dry environment and not in direct sunlight.

Health & Safety considerations

- When mixing any of the dry powder products, wear a respirator.
- Wear eye protection at all times. If eye contact occurs, irrigate eye with clean water and seek immediate medical attention.
- If any of the materials are swallowed, seek immediate medical attention.



Styjl
Kyrkängsgatan 6
SE 503 38 Borås
Sweden
Phone +46 (0)33 430 22 00
info@styjl.com

**Crafted
Acoustics**