

Product Data Sheet

Fellert Even Better Acoustical Coating

Product Description

The Even Better Acoustical Coating is a specialty coating designed for all types of acoustical ceilings. It can be used both on new installations to create a wide range of colors and on old ceilings for restoration purposes. When applied correctly, the coating does not decrease the acoustical absorption.

Installation

Mix thoroughly before use. Estimated drying time 20-30 minutes.

The product will be completely cured after 24 hours.

MAKE SURE TO READ THE INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

Properties

Water based. Non Toxic. Content: Calcium Carbonate, Titanium Dioxide, Aluminum silicate.

Packaging: 18 litre (4,8 US gallons) per pail.

Coverage: Even Better Secern finish: approx. 80 sqm (861 sqft)

Even Better Sahara finish: approx. 100 sqm (1076 sqft)

Even Better Silk finish: approx. 120 sqm (1292 sqft)

An air-mix spray gun (like the Kremlin 30:25) shall be used.

Storage

Store in enclosed dry environment. Avoid freezing.

Keep away from direct sunlight.



Styjl
Kyrkängsgatan 6
SE 503 38 Borås
Sweden
Phone +46 (0)33 430 22 00
info@styjl.com

Crafted Acoustics