

Product Data Sheet

Fellert Even Better Board Adhesive

Product Description

Used for bonding the Even Better Acoustical Board to drywall, existing plaster, concrete or previously painted surface.

Installation

Ensure that the surfaces are clean and dry.

Apply the adhesive on the back of the boards with 6x6 mm or 1/4" x 1/4" notched trowel.

Press together the surfaces to be glued before a film forms on the glue.

Open time 10-20 minutes. Depending on worksite conditions

Maximum strength after 1-5 days. Depending on worksite conditions.

Recommended worksite conditions, +18-20°C, below 90% RH (64-68°F, below 90% RH)

Minimum application temperature +10°C (50°F)

Properties

Contents: Acrylic dispersion adhesive.

Packing: 15 kg (33 lbs)

Handle instructions: Use safety goggles to avoid glue splashing into the eyes.

Wash your hands after use.

Flat coverage: 14-20 sqm (150-210 sqft)

Curved coverage: 10-12 sqm (107-129 sqft)

Storage

Stored dry without exposure to sunlight and at normal room temperature.

Storage time: (from +5°C to +25°C)(from +41°F to +77°F)

18 months. After long time storage stir before use.



Styjl
Kyrkängsgatan 6
SE 503 38 Borås
Sweden
Phone +46 (0)33 430 22 00
info@styjl.com

Crafted Acoustics