



CONMARBLE
NATURAL FINISHES



TECHNICAL DATA SHEET

ADDASTONE THIXOTROPIC AGENT

Thickening Filler

A CONMARBLE NATURAL FINISHES SYSTEM · RESIN-BOUND & RESIN-BONDED SURFACING

MANUFACTURED BY



Addagrip Terraco Ltd · United Kingdom

[VIEW OUR PROFILE](#)

[CONMARBLE.COM](https://conmarble.com)

BUILDING LAYERS BY CONMARBLE – Tabqat Albunyan Company For Contracting - CR: 7041240065
Showroom Location : Al Urubah Road, Al Olaya, PMV69+7V, City of Riyadh 12333, Saudi Arabia
Email: ahmad@conmarble.com, Insta: @conmarble, Tel: KSA +966 547 888 809 · QA +974 5573 7641

JULY 2026

OVERVIEW

ADDASTONE THIXOTROPIC AGENT is a polyethylene filler that can be added to **PU Addastone Resin** to reduce the resin from soaking into asphalt surfaces and to aid on sloped areas.

TECHNICAL DATA

Product	Thickening filler
Density	0.93g/cm ³
Packaging	Supplied in 10kg units
Storage	12 months in original unopened containers.

MIXING & APPLICATION

The **ADDASTONE THIXOTROPIC AGENT** should be added to the mixed **PU Addastone Resin** Part 'A' and 'B' at a rate of 0.5-1% per 20kg unit to achieve a creamy thickened consistency.

1. Cut a hole in one of the Part A lids – big enough to fit the drill paddle through.
2. Using the provided empty 1ltr bucket – add between 1-2 loads (dependant on ambient conditions) into the Part A carefully. Part C is very light and will be airborne easily. The more you add the thicker the product becomes.
3. Place lid with the hole back onto the container and mix to a homogenous consistency.
Up to 1.5% addition (3 loads per 20kg resin) is the recommendation.
4. Then scrape contents of 'B' into the mixed container 'A+C' and mix thoroughly for a minimum of 2 minutes using a low-speed electric drill.

Use protective gloves and goggles. Failure to mix thoroughly will result in poor or non-cured material.

HEALTH & SAFETY

Before using this product, please ensure you have been supplied and have read carefully the following: -

1. The hazard label (complying with CLP – European Regulation (EC) No. 1272/2008 on Classification, Labelling and Packaging of substances and mixtures) applied to the container.
2. Safety Data Sheet

Avoid prolonged contact with eyes and skin. For detailed information refer to the relevant safety data sheet.

CLEANING OF EQUIPMENT & SKIN

Tools, brushes etc... should be cleaned immediately after use with water. For cleaning of hands/skin, use a deep cleaning soap with water. Please note if a rash appears seek medical attention.

DISPOSAL CONSIDERATIONS

When the material has hardened in the pot it is inert, and the label must be defaced. The container and remnant may be disposed of as normal industrial waste. Otherwise, the material must be disposed by a chemical waste company. Please consider the regional or national regulations regarding disposal.

For technical enquiries please contact your nearest representative:

ADDAGRIP
Tel: +44 (0)1825 761 333
E-mail: sales@addagrip.co.uk
Web: www.addagrip.co.uk / www.terraco.com