



CONMARBLE  
NATURAL FINISHES



TECHNICAL DATA SHEET

# EUPHORIA BIANCO

*Marble Chips & Sequins*

A CONMARBLE NATURAL FINISHES SYSTEM · DECORATIVE FINISHES

MANUFACTURED BY

GIORGIO GRAESAN  
and Friends

Giorgio Graesan & Friends · Italy

[VIEW OUR PROFILE](#)

[CONMARBLE.COM](https://conmarble.com)

**BUILDING LAYERS BY CONMARBLE** – Tabqat Albunyan Company For Contracting - CR: 7041240065  
Showroom Location : Al Urubah Road, Al Olaya, PMV69+7V, City of Riyadh 12333, Saudi Arabia  
Email: [ahmad@conmarble.com](mailto:ahmad@conmarble.com), Insta: [@conmarble](https://www.instagram.com/conmarble), Tel: KSA +966 547 888 809 · QA +974 5573 7641

JULY 2026

|                                       |                                         |          |            |
|---------------------------------------|-----------------------------------------|----------|------------|
| <b>GIORGIO GRAESAN</b><br>and Friends | DATASHEET<br><br><b>EUPHORIA BIANCO</b> | Code     | TDS2110_00 |
|                                       |                                         | Revision | 00         |
|                                       |                                         | Date     | 12/09/2023 |

#### 1. DESCRIPTION

**CARRARA MARBLE grits bonded with Resins and PAILLETES**, which give the product strong and eye-catching **SILVER** effect light reflections.

#### 2. USE

EUPHORIA is suitable for decorating various types of interior wall surfaces. It is easy to apply with the KIT/NUDO stainless steel spatula.

#### 3. SUBSTRATE PREPARATION

A correct preparation of the substrate is indispensable for the finish to show its qualities to the fullest. It is important to carry out the elimination of any poorly-anchored or powdery paint or plaster, being sure to wash or remove any mould or dust that may be present. Before applying PRIMUS NATURALE, the surface must be completely cohesive, otherwise, proceed with the application of an insulating primer, recommended especially in cases of walls in plasterboard.

In the case of application on tiles, after having removed any grease on the walls with denatured ethyl alcohol, level any large joints with localised grouting using PRIMUS AGGRAPPANTE, let it dry, then, with the KIT/I stainless steel trowel, apply a smooth and homogeneous coat of PRIMUS AGGRAPPANTE.

#### 4. APPLICATION METHOD

EUPHORIA is ready for use.

First, colour it by pouring in the ADDITIVO COLORANTE, already stirred, in the quantity indicated in the catalogue and mixed until there is complete uniformity of the colour, making sure that none of the uncoloured product remains on the bottom or sides of the bucket.

It can be applied by hand using the KIT/NUDO stainless steel spatula. Cyclically, if necessary, go back over it to even it out and compact it, smoothing it slightly.

To prevent the detachment of residual product flakes, a coat of VETRO LUCIDO can be applied after 24 hours using a PE13 roller.

#### 5. TOOL CLEANING

Cleaning of the tools should be performed immediately after use with water.

#### 6. PROTECTION AND CLEANING

EUPHORIA with the addition of a coat of VETRO LUCIDO is water-repellent and absolutely washable. To clean the walls, it is advisable to use LATTE DETERGENTE (50 ml diluted in 1 litre of water).

Alternatively, it can also be protected with IPER VETRO.

#### 7. SAFETY INDICATIONS AND HAZARD IDENTIFICATION.

The product does not require labelling in accordance with current regulations. Use the product according to current hygiene and safety regulations. After use do not disperse the containers in the environment. Allow the residues to dry well and treat them as special waste. Keep out of the reach of children. If swallowed, seek medical advice immediately and show the healthcare operator the container or label. Do not dispose of residue in sewers, waterways and soil.

For further information see the safety datasheet available on the website: **[www.giorgiograesan.it](http://www.giorgiograesan.it)**

|                                       |                        |          |            |
|---------------------------------------|------------------------|----------|------------|
| <b>GIORGIO GRAESAN</b><br>and Friends | DATASHEET              | Code     | TDS2110_00 |
|                                       | <b>EUPHORIA BIANCO</b> | Revision | 00         |
|                                       |                        | Date     | 12/09/2023 |

| TECHNICAL SPECIFICATIONS: APPLICATION |                                                                               |
|---------------------------------------|-------------------------------------------------------------------------------|
| Dilution                              | Ready to use                                                                  |
| Mixing                                | Always mix before use                                                         |
| Colouring                             | 169 colours in the catalogue (before use, eliminate any dry flakes and stir). |
| Tools                                 | KIT/NUDO stainless steel spatula                                              |
| Primer                                | PRIMUS NATURALE                                                               |
| Conditions of application             | From +10°C to +30°C with relative humidity <85%                               |
| Number of coats                       | 1                                                                             |
| Curing time                           | 24 hours at 20°C                                                              |
| Protective coating                    | VETRO LUCIDO (one coat) with PE3 brush                                        |
| Washability                           | Complete washing with LATTE DETERGENTE if protected with VETRO LUCIDO         |

| TECHNICAL SPECIFICATIONS: CONSUMPTION |                      |
|---------------------------------------|----------------------|
| PRIMUS SABBIA / PRIMUS NATURALE       | 6 – 7 sqm/litre      |
| EUPHORIA BIANCO                       | 1 m <sup>2</sup> /kg |
| VETRO LUCIDO                          | 7 – 8 sqm/litre      |

| COLOUR | KG 8  | KG 4  |
|--------|-------|-------|
| T1     | 168ml | 84ml  |
| T2     | 62ml  | 31ml  |
| T3     | 20ml  | 10ml  |
| T4     | 7ml   | 3.5ml |

| TECHNICAL SPECIFICATIONS: PRODUCT                                                                  |                                                                                                                                                                                                 |
|----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Composition                                                                                        | Carrara marble grit, acrylic copolymer in water emulsion, additives, fillers and prismatic fragments.                                                                                           |
| Specific weight                                                                                    | 1.25± 0.05 Kg/litre                                                                                                                                                                             |
| Ph                                                                                                 | 8.0                                                                                                                                                                                             |
| EU limit value (Dir. 2004/42/EC)<br>Cat. A/I: paints for decorative effects (water-based): 200 g/l | Maximum content 0.00 g/l                                                                                                                                                                        |
| Storage conditions                                                                                 | Store in a tightly closed paint bucket, even after use and after having cleaned the sides and lid of the bucket, keep in a cool and dry place within the temperature range of + 5°C and + 30°C. |
| Packaging                                                                                          | 8 – 4 kg                                                                                                                                                                                        |

Giorgio Graesan & Friends guarantees that the information on this datasheet is provided to the best of its experience and technical and scientific knowledge, however it cannot assume any responsibility for the results obtained with its use as the conditions of application are beyond its control. It is advisable to always check the actual suitability of the product for the specific case. This document cancels and replaces each previous datasheet. For further technical information contact **(+39) 02.9903951** or on **Whatsapp: (+39) 3371410335**.