



CONMARBLE
NATURAL FINISHES



Photography: Clayworks

TECHNICAL DATA SHEET

EXTERIOR RUSTIC FINISH

Natural Clay Plasters

A CONMARBLE NATURAL FINISHES SYSTEM · CLAY PLASTER

MANUFACTURED BY

Clayworks

Clayworks · United Kingdom

[VIEW OUR PROFILE](#)

[CONMARBLE.COM](https://conmarble.com)

BUILDING LAYERS BY CONMARBLE – Tabqat Albunyan Company For Contracting - CR: 7041240065
Showroom Location : Al Urubah Road, Al Olaya, PMV69+7V, City of Riyadh 12333, Saudi Arabia
Email: ahmad@conmarble.com, Insta: [@conmarble](https://www.instagram.com/conmarble), Tel: KSA +966 547 888 809 · QA +974 5573 7641

JULY 2026

Clayworks



Exterior Rustic finish

Clayworks Exterior Rustic is a coarser mineral exterior finish with pronounced texture and strong material presence. Its expressive surface brings depth and tactility to façades, grounding buildings in their surrounding environment and allowing the finish to weather naturally over time.

Designed to protect external substrates while remaining breathable, the finish supports long-term façade performance through moisture management and mineral durability.

Interior Rustic finish

Intended Design Use

- Intended for exterior environments exposed to weather
- Designed for long-term exterior performance when correctly detailed and maintained (25 years +)
- Well suited to façades where texture and material expression are a deliberate architectural choice
- Vapour permeable finish that allows moisture to move safely through the wall construction
- Performance achieved through detailing, substrate preparation, curing, and ongoing maintenance

Intended Use & Limitations

Suitable for exterior walls and façades. Not suitable for floors or horizontal walking surfaces. Not intended for use in permanently saturated conditions or areas subject to standing water. Careful consideration of junctions, copings, and drainage is essential.

Application & Substrates

Application: Use of a Clayworks Approved Applicator is strongly recommended. All Custom Finishes must be installed by an Approved Applicator.

Application Requirement:

Standard finishes: Professional Application

Custom finishes: Specialist Application

Coverage:

Stipple coat - 4.5m² per 25kg with thickness of 3mm.

Base coat - 1.6m² per 25kg with thickness of 8mm.

Top coat - 1.6m² per 25kg with thickness of 8mm.

Approximate Drying time: 2 Months

Substrates: Refer to the *Clayworks Design Details* datasheet for full substrate guidance.

Maintenance & Repair

Exterior Rustic finishes should be inspected periodically as part of routine façade maintenance. Localised repairs can be carried out using colour-matched material by a suitably trained professional, allowing the surface to be maintained over time without wholesale replacement.

Product Information

Composition: Mineral-based binder with graded aggregates, minerals, and natural pigments

Supply: 25kg bags

Country of Origin: UK (Cornwall)

Colours: 89 standard colours + custom matching

Warranty: 10 years manufacturer's warranty (subject to correct detailing, application, and maintenance)

Life Expectancy: 25 years + (subject to correct detailing, application, and maintenance)

Performance Data

Fire: Euroclass A1 Fire Rating to EN 13501 and EN 15824 international standards

Thermal Conductivity: Approx. 0.83 W/mK

Moisture Buffer Value : Vapour permeable; supports moisture movement through the wall build-up

Light Reflective Value: Available on request

Sustainability & Human Health

- Vapour permeable and breathable mineral finish
- Non-toxic composition
- No added VOCs
- Reduced embodied energy compared to conventional cementitious coatings
- Long-term durability through mineral carbonation and curing

Certifications & Reports

- [Fire Reports \(EN & ASTM\)](#)
- [Environmental Product Declaration \(EPD\)](#)

Health & Safety

As a powdered product, appropriate dust control measures should be taken during handling and mixing. A suitable dust mask should be worn. Standard site PPE should be used in accordance with local regulations.

Storage

Store unopened bags in dry conditions, protected from moisture and frost. Do not pierce bags. Once opened, unused material should be sealed in airtight containers and stored dry.

Disposal

Once cured, the material should be disposed of as inert mineral construction waste in accordance with local regulations. Packaging should be disposed of in accordance with local waste and recycling requirements.